



DALI POWER BY LEDVANCE

LIGHT MANAGEMENT
THAT SIMPLY FEELS GOOD





DISCOVER NOW

THE FULL DALI POWER FROM LEDVANCE

Top systems need top components. That's why LEDVANCE is presenting a new range of DALI components under the LEDVANCE brand for the first time – this range is bigger and better than ever before. The DALI-2 certified control units, sensors and pushbutton couplers come in a new design and with extra functions and are a perfect match for the LEDVANCE DALI luminaires. Furthermore they perfectly integrate with other DALI systems in the market.

LIGHT MANAGEMENT IS VIVARES

VIVARES Light Management Systems (LMS) systems by LEDVANCE adjust the lighting in working environments individually, flexibly and in line with people's natural lighting needs. What's more, controlling the lights via sensors maximises savings.

EVERYTHING FROM A SINGLE SOURCE – SERVICE FROM LEDVANCE

Are you looking for help with configuring your lighting systems – tailored to your individual project, from single rooms to complete floor solutions? Then you've come to the right place. LEDVANCE offers a unique all-round service and is your competent contact for all aspects of your project. See for yourself!

ANY QUESTION? TALK TO US.


Are you interested in our services for your projects? Our project business experts are happy to advise you. You can reach us at contact@ledvance.com or by phone on +49 89 780673-600

All information of successful projects can be found here: ledvance.com/projects



LIGHT MANAGEMENT SYSTEMS – TOP BENEFITS

- 1 **Individual, customisable light setup to increase the comfort level in working environments**
 - Select the preferred brightness for your needs.
 - Adjust the light colours to your mood from warm to cold.
- 2 **Maximise energy cost savings of up to an additional 50%* beyond LEDification and prolong luminaire's life**
 - Sensors taking over the light control: depending on presence and/or movement light will switch on and off.
 - If daylight is available from windows the artificial light level in the room is reduced.
 - Prolonged lifetime of luminaires due to decrease in hours of operation.
- 3 **Human centric lighting – the advanced well-being light**
 - Benefit from positive effects to increase productivity and healthiness and reduce sick leave days.
 - Examples based on CBRE Healthy Offices study: Productivity +10 %, Healthiness +52 %.



ONE ROOM – MANY SOLUTIONS



SINGLE ROOM

▶ JUST WIRE AND BE HAPPY

Your DALI single room plug & play control units:

- MCU SELECT DALI-2 and MCU TOUCH DALI-2

▶ JUST TAKE FLEXIBLE CONTROL

Your DALI single room control units for automated or manual control:

- FLEX CU DALI-2

MANY ROOMS – ONE SOLUTION



MULTI ROOM

▶ JUST THINK BIGGER

Your DALI MULTI ROOM app- or software-operated control units:

- FLEX CONTROL UNIT IoT DALI-2 and cloud services

▶ JUST DETECT

Your new LEDVANCE sensor range:

- SENSOR DALI-2 LS-PD versions and pushbutton coupler

WE POINT THE WAY:

Look out for these symbols and let us guide you.



MANUAL LIGHT CONTROL



AUTOMATED LIGHT CONTROL



JUST WIRE AND BE HAPPY

SINGLE ROOM PLUG & PLAY CONTROL UNITS

BESTSELLER REASONS

- 1. Plug & play:** ready to use. Just wire and be happy
- 2. Pre-programmed functions for manual room lighting:** ON/OFF, DIM, TW, MEMORY. No app, software or registration required.
- 3. High quality glass controllers** with touch display
- 4. Exchangeable front cover** thanks to broad compatibility with most popular lighting frames in the market
- 5. Surface mount frame** accessory for wall-mounted installations



Good lighting can be so simple. For example, with LEDVANCE's plug & play control units. They ensure perfect control at all times in single rooms with an area of up to 200m² and up to 25 luminaires. And they're user-friendly and come in ultra-modern designs.



DALI-2 CONTROLLER FOR SINGLE ROOM APPLICATIONS UP TO 200 SQM ROOM SIZE AND 25 LUMINAIRES

COMPATIBILITY OF MCU SELECT DALI-2 EXC* TW WITH VARIOUS FRONT COVERS

Supplier	Design-Line
Busch-Jaeger (apply enclosed axle adapter)	Reflex-SI, Reflex-SI-Linear, Reflex SI/SI Linear, Busch-Duro 2000® SI, Busch-Duro 2000® SI Linear
SIEMENS	Delta-i-system, Delta vita, Delta profil, Delta stil
SCHNEIDER	Exact Design, Exact Primo, Exact Basis, Exact Fest
BERKER	Q1, Arsys
GIRA	S Farbe, System55
JUNG	LS Plus, LS Design, Ein Plus, Ein 500, AS500

EVERYTHING AT A GLANCE: PRODUCTS AND KEY FEATURES

Control unit	MCU SELECT Digital rotary dimmer	MCU SELECT TW Digital rotary dimmer	MCU SELECT EXC* TW Digital rotary dimmer	MCU TOUCH Digital touch dimmer	MCU TOUCH TW Digital touch dimmer
Product picture					
EAN	4058075837485	4058075837508	4058075837522	4058075837546	4058075837560
Number of luminaires/lights	25 up to 100 with up to 4 MCU controllers	25 up to 100 with up to 4 MCU controllers	25 up to 100 with up to 4 MCU controllers	25 up to 100 with up to 4 MCU controllers	25 up to 100 with up to 4 MCU controllers
Support plug and play, no commissioning of basic functions necessary	●	●	●	●	●
ON/OFF	●	●	●	●	●
DIM	●	●	●	●	●
Tunable White	—	●	●	—	●
MEMORY	●	●	●	●	●
DALI bus powered	●	●	●	●	●
Exchangeable front cover	—	—	●	—	—
DALI-2 certified	●	●	●	●	●

* Exchangeable cover



TURNING IT ON MCU SELECT DALI-2



MCU SELECT
DALI-2 EXC TW

MCU SELECT
DALI-2


MCU SELECT
DALI-2 TW



PRODUCT FEATURES:

- Flush-mounted control unit for manual light control
- Mains powered (active mode) or DALI powered (passive mode) operation
- No cloud, no registration, no app required
- Dimming and switching of up to 25 DALI luminaires
- Up to 4 control units can be connected in parallel to set up multiple control points
- Can be combined with standard presence/ movement detectors

SO INTUITIVE: MANUAL LIGHT CONTROL FOR SINGLE ROOMS




FEATURES AT A GLANCE:

- On/off at the touch of a button
- Dim by turning
- Save lighting settings
- Delete power-on brightness
- Limit minimum brightness
- Reset minimum brightness



EXTRA TUNABLE WHITE FEATURES:

- Change colour temperature
- Limit minimum and maximum colour temperature
- Reset colour temperature limits





CONTROL MADE EASY

MCU TOUCH DALI-2



MCU TOUCH
DALI-2




MCU TOUCH
DALI-2 TW

PRODUCT FEATURES:

- Flush-mounted control unit for manual light control
- Mains powered (active mode) or DALI powered (passive mode) operation
- No cloud, no registration, no app required
Pre-programmed light colours (TW version) and DIM level (monochromatic version)
- Dimming and switching of up to 25 DALI luminaires
- Up to 4 control units can be connected in parallel to set up multiple control points

MCU TOUCH DALI-2


Pre-programmed DIM levels



4 Memory buttons (Scene S1 to S4)
Push 10 sec to programme individual light settings

MCU TOUCH DALI-2 TW


Pre-programmed light colours



4 MEMORY buttons (Scene S1 to S4)
Push 10 sec to programme individual light settings

ACCESSORY: SURFACE MOUNT FRAME

- Surface mount frame for MCU SELECT and MCU TOUCH products
- Suitable for walls where installations in flush-mounted boxes are not possible



Compatible with
MCU SELECT & TOUCH family



JUST TAKE FLEXIBLE CONTROL

SINGLE ROOM CONTROL UNITS FOR AUTOMATED AND MANUAL LIGHT CONTROL

BESTSELLER REASONS

1. Ready to use with pre-programmed lighting control features
2. Individual application-oriented programming via app
3. Real-time clock for timeline settings
4. Pre-programmed BIOLUX HCL for biologically effective light
5. Compatible with sensors and/or pushbutton couplers for automated and/or manual lighting control

LEDVANCE helps you find the perfect setting. Our automatically and manually adjustable DALI-2 control units make controlling your lights even easier – in single rooms of up to 250m² with up to 32 luminaires and up to 4 sensors and pushbutton couplers.

DALI-2 CONTROLLER FOR SINGLE ROOM APPLICATIONS UP TO
- 250 SQM ROOM SIZE
- 32 LUMINAIRES
- 4 SENSORS/PUSHBUTTON COUPLERS




SINGLE ROOM



FLEX CU
FLUSH MOUNT
DALI-2 TW



FLEX CU
DALI-2 TW



FLEX CU RTC
DALI-2 HCL TW

EVERYTHING AT A GLANCE: PRODUCTS AND KEY FEATURES

Control unit Function	FLEX CU FLUSH MOUNT DALI-2 TW	FLEX CU DALI-2 TW	FLEX CU RTC DALI-2 HCL TW
Product picture			
EAN	4058075841901	4058075843844	4058075841925
Number of luminaires/components	32	32	32
Support plug and play, commissioning of basic functions not necessary	●	●	●
Sensor for daylight control	●	●	●
Sensor for presence control	●	●	●
Groups	●	●	●
Scenes	●	●	●
ON/OFF	●	●	●
DIM	●	●	●
Tunable white	●	●	●
Human Centric Lighting (HCL)	—	—	●
Schedules	—	—	●
App control	●	●	●
DALI-2 certified	●	●	●
Swarm function	●	●	●



**SINGLE ROOM CONTROL
UNITS: AUTOMATED AND
MANUAL LIGHT CONTROL**



PRODUCT BENEFITS:

- Control of light via smartphone
- Adjustment of all settings via smartphone
- Plug & play: basic features usable without app
- Simplified startup thanks to predefined operation modes
- Intuitive manual dimming, switching and changing of colour temperature

ALWAYS WELL CONNECTED FLEX CU FLUSH MOUNT DALI-2 TW

PRODUCT FEATURES:

- Suitable for installation in flush-mounted boxes
- One DALI output channel (broadcast or groupcast)
- DALI bus powered
- Up to 32 DALI luminaires connectable
- Supports up to 4 DALI sensors and pushbutton couplers



FEEL-GOOD CONTROL FLEX CU DALI-2 TW AND FLEX CU RTC DALI-2 HCL TW



PRODUCT FEATURES:

- One DALI output channel (broadcast or groupcast)
- DALI bus powered
- Up to 32 DALI luminaires connectable
- Supports up to 4 DALI sensors and pushbutton couplers
- Plug & play: basic features usable without app
- Simplified startup thanks to predefined operation modes
- Up to 4 groups separately controllable
- Control of standard white or tunable white light according to DALI device type 8 (DT8)
- Endcap with strain relief function included in product delivery

PRODUCT BENEFITS:

- Real-time clock for time-of-day-dependent automatic control of brightness and colour temperature
- Pre-programmed BIOLUX HCL
- Manual light control via smartphone
- Adjustment of all settings via smartphone

TWO APPS FOR TWO APPLICATIONS

Both Apps are compatible with FLEX CU DALI-2 TW, FLEX CU RTC DALI-2 HCL TW and FLEX CU FM DALI-2 TW. The DALI CONTROL App is made for manual light control. With the DALI CONFIG App the individual lighting creation is supported.


All products can be configured and controlled with a smartphone or tablet via Bluetooth interface.



CONTROL APP



CONFIGURATION APP





JUST THINK BIGGER

DALI-2 CONTROL UNIT FOR MULTI ROOM APPLICATIONS


BESTSELLER REASONS

1. Individual application-oriented programming via app/software
2. Remote access for changes in the installation from every location in the world
3. Pre-programmed BIOLUX HCL for biologically effective light
4. Compatible with sensors and/or pushbutton couplers for automated and/or manual lighting control
5. Compatible with VIVARES Cloud Services for energy monitoring and savings

The right control also allows you to create an individual lighting experience in open-plan offices. Thanks to the new DALI-2 control unit for multi room applications, you now have a choice of tailor-made components for this.

► Currently available

► Available from December 2024



OSRAM DALI PRO 2
IoT LDVV
EAN: 4052899627079



FLEX CU IoT
DALI-2 HCL TW



DALI-2 CONTROLLER FOR MULTI ROOM APPLICATIONS UP TO
– 1,000 SQM ROOM SIZE
– 128 LUMINAIRES
– 126 SENSORS AND/OR PUSHBUTTON COUPLERS

PRODUCT FEATURES:

- Controllers with two DALI lines for up to 128 DALI luminaires and up to 126 DALI components
- 2 x 16 groups and different scenes possible
- For larger objects, up to 8 controllers can be connected to each other in a network

OUR HIGHLIGHT: FLEX CU IoT DALI-2 HCL TW

- **LAN INTERCONNECT:** up to 8 controllers can be connected in one network
- **Emergency light:** automated testing and reporting of emergency lighting installations
- **Remote access:** changes in the installation without the need to visit the site
- **Cloud API:** connection of 3rd party cloud possible
- **BIOLUX Human Centric Lighting:** for biologically effective light
- **VIVARES Cloud Services:** monitoring, fault diagnosis and predictive maintenance via remote access for registered users

AVAILABLE FROM
DECEMBER 2024





JUST THE BEST OPTION VIVARES CLOUD SERVICE

A service that is definitely worth it. The VIVARES cloud allows you to access the data of your lighting system from anywhere. An intuitively controllable dashboard and convenient filters for on-demand analysis help you operate your system even more reliably, energy-efficiently and cost-effectively.

ALWAYS UP-TO-DATE OPTIONAL IoT VALUE-ADDED SERVICES

- Optimise energy consumption, reduce costs
- Reduce maintenance costs – adapt the maintenance cycle to actual demand
- Diagnose faults from any location – all you need is internet access and a tablet/PC
- Future-proof with the option of new services

SERVICES FOR EVEN MORE EFFICIENT OPERATION



ENERGY MONITORING

Monitor the system's energy consumption and optimise for even more savings



DASHBOARD

Keep an eye on everything with the user-friendly dashboard: energy monitoring, remote diagnosis, predictive maintenance



MAINTENANCE ASSISTANT

Users of the lighting installation can check the system's status anytime via remote access: lifetime information and fault diagnosis allow maintenance to be predictive

-86%

According to the dashboard that monitors the LEDVANCE headquarter office it is possible to save up to even 86% of energy* when upgrading to LED and using light management that works with occupancy detection and daylight harvesting.



*Compared to a conventional fluorescent solution (on/off); Calculation based on 6 months of real data from LEDVANCE EM/MA dashboard; The kWh per day are based on 3 months of data history; Full operation of 12 h per day (7am to 7pm).


VIVARES CLOUD SERVICE TUTORIAL

Further information at:
<https://www.youtube.com/watch?v=EFwStAgcoqE>



VIVARES CLOUD SERVICE REGISTRATION

VIVARES Cloud Service is free of charge for the first 6 months after registration. Register now! ledvance.com/vivares-cloudservice





JUST DETECT THE NEW LEDVANCE COMPONENTS DALI-2 INPUT DEVICES

BESTSELLER REASONS

1. Plug & play
2. Powered via DALI bus
3. Function indicator LED
4. Shutter included (sensor) for adjustment of detection area
5. Through-loop wiring for simple installation (pushbutton coupler)

Whether it's sensors or pushbutton couplers – it's the components that significantly determine the quality and user-friendliness of a light management system. With our comprehensive range of sensors, you're always making the right choice.

FOR SINGLE & MULTI ROOM APPLICATIONS
- SENSOR FAMILY
- PUSHBUTTON COUPLER



SENSOR DALI-2 LS-PD-6 IR CI



SENSOR DALI-2 LS-PD-8 IR CI



SENSOR DALI-2 LS-PD-40X5 IR CI




SENSOR DALI-2 LS-PD-24 IR CM

LMS DALI-2 INPUT DEVICE FOR SENSOR-CONTROLLED LIGHT

PRODUCT FEATURES:


- Selection of different sensor types for office, corridor, warehouse and parking applications
- Occupancy detection via passive IR element
- Light sensing up to 2,000 lx
- DALI bus powered
- Optional SENSOR CM KIT for surface mounted installation



PUSHBUTTON COUPLER DALI-2 FOR MANUAL LIGHT CONTROL

PRODUCT FEATURES:

- Suitable for installation in flush-mounted boxes
- DALI bus powered
- 4 independent pushbuttons can be connected
- Multiple couplers connectable to the same DALI line



PUSHBUTTON COUPLER DALI-2



SMART SENSOR SOLUTIONS: EFFICIENT AND FLEXIBLE LIGHT CONTROL


SENSOR DALI-2 LS-PD-6 IR CI

HIGHLIGHTS:

- DALI-2 certified input device (303, 304)
- Modern reduced design
- Occupancy detection via passive IR element

BENEFITS:

- Ceiling integration with integrated cable clamp
- More than 50,000h lifetime @ $t_a = 50^\circ\text{C}$ system
- Powered via DALI bus




SENSOR DALI-2 LS-PD-8 IR CI

HIGHLIGHTS:

- Wide detection range
- DALI-2 certified input device (303, 304)
- Modern reduced design
- Occupancy detection via passive IR element

BENEFITS:

- Ceiling integration with integrated cable clamp
- More than 50,000h lifetime @ $t_a = 50^\circ\text{C}$ system
- Powered via DALI bus




SENSOR DALI-2 LS-PD-40X5 IR CI

HIGHLIGHTS:

- Wide detection area optimised for corridors (up to 40m)
- DALI-2 certified input device (303, 304)
- Occupancy detection via passive IR element

BENEFITS:

- Ceiling integration with integrated cable clamp
- More than 50,000h lifetime @ $t_a = 50^\circ\text{C}$ system
- DALI powered




SENSOR DALI-2 LS-PD-24 IR CM

HIGHLIGHTS:

- Wide detection area of up to 24m
- IP54 protection for underground parking
- Occupancy detection via passive IR element

BENEFITS:

- Ceiling integration with integrated cable clamp
- More than 50,000h lifetime @ $t_a = 50^\circ\text{C}$ system
- DALI powered



ACCESSORY FOR SENSORS: SENSOR CM KIT LEDVANCE

HIGHLIGHTS:


- Enables surface and recessed ceiling mounting in addition to the standard use of the product
- Surface mounting will be protection class IP54
- Recessed ceiling mounting kit includes spring clips and integrated cable clamp

COMPATIBILITY:


- The following sensors will be supported:
- SENSOR DALI-2 LS-PD-8 IR CI EAN 4058075841949
 - SENSOR DALI-2 LS-PD-40X5 IR CI EAN 4058075843868



SENSOR CM KIT LS-PD-8



SENSOR CM KIT LS-PD-24 / -40x5




PERFORMANCE – A COMPARISON

Control unit	DALI-2 LS-PD-6 IR CI	DALI-2 LS-PD-8 IR CI	DALI-2 LS-PD-40X5 IR CI	DALI-2 LS-PD-24 IR CM
Product picture				
DALI-2 input device, infrared presence detector with 6m movement detection	DALI-2 input device, infrared presence detector with 6m movement detection	DALI-2 input device, infrared presence detector with 8m movement detection	DALI-2 input device, infrared presence detector with 16 x 3 m movement detection	DALI-2 input device, infrared presence detector with 24 m movement detection
Mounting height sensor	2.5m 3.0m	2.5m 3.0m	2.5m 3.0m	2.5m 3.0m
Tangential motion detection	3.0m 3.0m	4.0m 4.5m	L 40.0m/W 5.0m L 30.0m/W 5.0m	5.0m 5.0m
Radial presence detection	6.0m 8.0m	8.0m 9.0m	L 16.0m/W 3.0m L 19.0m/W 3.5m	24.0m 24.0m
Shutter included to select detection area	—	✓	✓	✓
Surface mount kit available	—	✓	✓	Not relevant
Performance/price ranking	Value	Advanced	Advanced	Advanced

A MOVE IN THE RIGHT DIRECTION


The detection range of motion sensors can be divided into two areas:



SENSOR ABBREVIATIONS

- LS: Light sensor
- PD: Presence detection
- IR: Infrared
- CI: Ceiling integration
- CM: Ceiling mounting

DALI-2 CONTROL UNITS



Product name	EAN (GTIN)	V	Hz	Ta		MAX. NO. OF GROUPS	APP	L x W x H [mm] Ø x H [mm]	No.	
MANUAL CONTROL UNITS										
Manual control unit for up-to 25 lights										
MANUAL CONTROL UNIT SELECT DALI-2	4058075837485	100...240	50...60	-20...+50 °C	Integrated in flush device box	25	1	Ready to use	80 x 80 x 53	1
Manual control unit for up-to 25 lights, enables Tunable White lighting										
MANUAL CONTROL UNIT SELECT DALI-2 TW	4058075837508	100...240	50...60	-20...+50 °C	Integrated in flush device box	25	1	Ready to use	80 x 80 x 53	2
Manual control unit for up-to 25 lights, enables Tunable White lighting, exchangeable cover										
MANUAL CONTROL UNIT SELECT DALI-2 EXCHANGEABLE COVER TW	4058075837522	100...240	50...60	-20...+50 °C	Integrated in flush device box	25	1	Ready to use	80 x 80 x 53	3
Manual control unit with touch display for up-to 25 lights										
MANUAL CONTROL UNIT TOUCH DALI-2	4058075837546	100...240	50...60	-20...+50 °C	Integrated in flush device box	25	1	Ready to use	86 x 86 x 41	4
Manual control unit with touch display for up-to 25 lights, enables Tunable White lighting										
MANUAL CONTROL UNIT TOUCH DALI-2 TW	4058075837560	100...240	50...60	-20...+50 °C	Integrated in flush device box	25	1	Ready to use	86 x 86 x 41	5
ACCESSORY										
Surface mount frame for MCU SELECT and MCU TOUCH product families										
SURFACE MOUNT FRAME	4058075843561	—	—	—	Surface mounting	—	—	—	80 x 80 x 42	6

FITTING PRODUCTS

Product name	EAN (GTIN)	Product type	Fitting EAN
ACCESSORY			
SURFACE MOUNT FRAME	4058075843561	Surface mount frame for MCU SELECT and MCU TOUCH product families	4058075837485, 4058075837508, 4058075837522, 4058075837546, 4058075837560



Further information about the VIVARES products can be found at [ledvance.com/vivaresproducts](https://www.ledvance.com/vivaresproducts)

¹ Refer to www.ledvance.com/guarantee for precise conditions

DALI-2 CONTROL UNITS



1



2



3

Product name	EAN (GTIN)	V	Hz	Ta		NO. OF OUTPUTS	MAX.	MAX.	NO. OF GROUPS	APP	L x W x H [mm] Ø x H [mm]	No.
--------------	------------	---	----	----	--	----------------	------	------	---------------	-----	------------------------------	-----

FLEX CONTROL UNITS

Interface for standard lighting switches, control of up to 32 lights and up to 4 sensors/pushbutton couplers, installation in standard flush mounted boxes, enables Tunable White lighting

FLEX CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075841901	220...240	50...60	-20...+60 °C	Integrated in flush device box	1	32	4	4	App (Android/ iOS)	49 x 48 x 22	
---	---------------	-----------	---------	--------------	--------------------------------	---	----	---	---	--------------------	--------------	--


Control unit for up-to 32 lights and up-to 4 sensors/pushbutton couplers

FLEX CONTROL UNIT DALI-2 TW	4058075843844	220...240	50...60	-20...+60 °C	Integrated in flush device box	1	32	4	4	App (Android/ iOS)	119 x 30 x 21	
-----------------------------	---------------	-----------	---------	--------------	--------------------------------	---	----	---	---	--------------------	---------------	--

Control unit for up-to 32 lights and up-to 4 sensors/pushbutton couplers, integrated real-time clock

FLEX CONTROL UNIT REAL-TIME-CLOCK DALI-2 HCL TW	4058075841925	220...240	50...60	-20...+60 °C	Integrated in flush device box	1	32	4	4	App (Android/ iOS)	119 x 30 x 21	
---	---------------	-----------	---------	--------------	--------------------------------	---	----	---	---	--------------------	---------------	--

DALI-2 PUSHBUTTON COUPLER



Product name	EAN (GTIN)	V	Hz	Ta		L x W x H [mm] Ø x H [mm]
--------------	------------	---	----	----	--	------------------------------

DALI-2 PUSHBUTTON COUPLER

DALI-2 interface to integrate standard lighting switches in DALI systems

PUSHBUTTON COUPLER DALI-2	4058075837607	16	0	-20...+50 °C	Integrated in flush device box	50 x 43 x 15	
---------------------------	---------------	----	---	--------------	--------------------------------	--------------	--



Further information about the VIVARES products can be found at ledvance.com/vivaresproducts

¹ Refer to www.ledvance.com/guarantee for precise conditions

DALI-2 SENSORS



Product name	EAN (GTIN)	V	Hz	Beam angle	Lx	lx/m	Ta	Mounting	COLOR	L x W x H [mm] Ø x H [mm]	Light No.	
SENSORS												
DALI-2 input device, infrared presence detector with 6 m movement detection												
SENSOR DALI-2 LIGHT/PRESENCE-6 INFRARED CEILING INTEGRATION	4058075837621	16	0	360°	6 m	—	3.7	0...+40 °C	Ceiling integration	White	83 x 32	1
DALI-2 input device, infrared presence detector with 8 m movement detection												
SENSOR DALI-2 LIGHT/PRESENCE-8 INFRARED CEILING INTEGRATION	4058075841949	10...22.5	0	360°	8 m	5...2000	4	-20...+45 °C	Ceiling integration	White	105 x 67	2
DALI-2 input device, infrared presence detector with 40 x 5 m movement detection												
SENSOR DALI-2 LIGHT/PRESENCE-40X5 INFRARED CEILING INTEGRATION	4058075843868	10...22.5	0	360°	40 x 5 m	5...2000	4	-20...+45 °C	Ceiling integration	White	105 x 67	3
DALI-2 input device, infrared presence detector with 24 m movement detection												
SENSOR DALI-2 LIGHT/PRESENCE-24 INFRARED CEILING MOUNTING	4058075843882	10...22.5	0	360°	24 m	5...2000	4	-20...+45 °C	Surface mounting	White	105 x 67	4
ACCESSORY												
Adapter for surface mounting installations												
SENSOR CEILING MOUNTING KIT	4058075843905	—	—	—	—	—	—	—	Surface mounting	White	68 x 68 x 44	5

FITTING PRODUCTS

Product name	EAN (GTIN)	Product type	Fitting EAN
ACCESSORY			
SENSOR CEILING MOUNTING KIT	4058075843905	Adapter for surface mounting installations	4058075841949, 4058075843868

ONE FAMILY, TWO SYSTEMS, ALL OPTIONS

Our new generation of DALI-2 IoT luminaires makes it easier than ever to wow your customers with modern light management solutions. The luminaire family has become more versatile, powerful and efficient, and is fit for both Tunable White and BIOLUX HCL applications. Discover the possibilities: www.ledvance.com/lms



Further information about the VIVARES products can be found at ledvance.com/vivaresproducts

¹ Refer to www.ledvance.com/guarantee for precise conditions

ABOUT LEDVANCE

With business activities in over 140 countries, LEDVANCE is one of the world's leading general lighting companies. Emerging from OSRAM's general lighting division, LEDVANCE's portfolio includes LED lamps and luminaires, intelligent lighting products, traditional lamps and renewable energy solutions.
#POWERTHROUGHLIGHT



LEDVANCE

LEDVANCE GmbH
Parkring 1-5
85748 Garching
Germany