

# PRODUCT DATASHEET LED Sensor Batten 320mm 4W 3000K

LED Sensor Batten | Slim LED Batten luminaire with integrated Sensor for on/off switching



#### Areas of application

- Offices
- Undercabinet lighting
- Kitchens

#### Product benefits

- Attractive and functional design for office applications
- Touchless switching thanks to integrated sensor

#### Product features

- Integrated motion sensor



# TECHNICAL DATA

# Electrical data

Nominal wattage	4.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	32.000 mA
Inrush current time T <sub>h50</sub>	182 μs
Max. number of luminaires per miniature circuit breaker B16	56
Max. number of luminaires per miniature circuit breaker C16	56
Power factor $\lambda$	> 0.5
Total harmonic distortion	110 %
Protection class	П
Operating mode	Integrated LED driver

# Photometrical data

Luminous flux	400 lm
Total luminous flux of contained light sources	450 lm
Luminous efficacy	100 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 5 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	180 °

# Dimensions & Weight

Length	313.00 mm
Width	28.00 mm
Height	36.00 mm
Product weight	77.00 g



#### Materials & Colors

Product color	White
Housing color	White
Body material	Plastic
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Application environment	Indoor
With light source	Yes
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	50000 h <sup>1)</sup>
Number of switching cycles	100000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

#### Sensor

Type of sensor	Movement	
Certificates & Standards		
Standards	CE	
Luminaire with limited surface temperature, "D sign"	No	
Ball shot safe	No	

#### **EQUIPMENT / ACCESSORIES**

- Mounting screws and dowels included

# Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

#### **DOWNLOAD DATA**

	Documents and certificates Document name	
PDF	User instruction / safety instructions	LED BATTEN SENSOR
PDF	Legal information	Safety insert G11220499
PDF	Declarations of conformity	CE Declaration LED BATTEN SENSOR

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854532498	Folding box 1	32 mm x 62 mm x 523 mm	166.00 g	1.04 dm <sup>3</sup>
4099854532504	Shipping box 8	535 mm x 140 mm x 155 mm	1652.00 g	11.61 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.