

# PRODUCT DATASHEET ENDURA Classic Square UpDown White

ENDURA® Classic Square | Outdoor Endura Classic square with socket GU10



## Areas of application

- Entrance lighting
- Patios, balconies
- Building facades

#### Product benefits

- High flexibility in the choice of the light source thanks to GU10 socket
- Easy and quick installation
- High-quality materials

## **Product features**

- Die-cast aluminum housing



# TECHNICAL DATA

# Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	1
Operating mode	Mains voltage

# Dimensions & Weight

Length	68.00 mm
Width	150.00 mm
Height	92.00 mm
Product weight	550.00 g



# Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44/IP44
Protection class IK (shock resistance)	IK04
Dimmable	No
Mounting type	Surface
Mounting location	Wall

Application environment	Outdoor
With light source	No
Replaceable light source	No
Holder designation	GU10

# **Emergency lighting**

Type of emergency operation test	None
----------------------------------	------

#### Certificates & Standards

Standards		CE / UKCA
I	Luminaire with limited surface temperature, "D sign"	No
E	Ball shot safe	No

## Additional product data

Product remark	Maximum bulb wattage: 35 W
Number of illuminants	2

#### **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

#### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

#### **DOWNLOAD DATA**

	Documents and certificates Document name		
User instruction / safety instructions		ENDURA CLASSIC SQUARE UP DOWN	
PDF	Legal information	Safety insert G11219578	
PDF	Declarations of conformity	ENDURA CLASSIC	
PDF	Declarations of conformity UKCA Fixed LUM without EMC		

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854447846	Folding box 1	77 mm x 102 mm x 162 mm	631.00 g	1.27 dm <sup>3</sup>
4099854447853	Shipping box	245 mm x 120 mm x 352 mm	4050.00 g	10.35 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.