

PRODUCT DATASHEET LED TUBE T8 EM CONNECTED 1500 mm 24W 840

LED TUBE T8 EM CONNECTED | LED tube for electromagnetic control gear (CCG) works with Connected Sensors, shatterproof



Areas of application

- General illumination within ambient temperatures from -20...+50 °C
- Parking lots, warehouses, production areas
- Industry
- Offices

Product benefits

- No bending thanks to glass technology
- Shatter protection thanks to special PET coating
- Short payback period thanks to low energy consumption and maintenance costs

Product features

- Network protocol: ZigBee 3.0 (2.4 GHz mesh network)
- LED TUBE T8 EM Connected can be only operated with LEDVANCE Connected Sensor





TECHNICAL DATA


Electrical data

Nominal wattage	24 W
Construction wattage	24.00 W
Nominal voltage	220240 V
Operating mode	CCG, AC Mains
Nominal current	107 mA
Type of current	AC
Inrush current	3 A
Suitable for DC input	Yes
Input voltage DC	186260 V ¹⁾
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	65
Max. lamp number on MCB B10 A - CCG without compensation	65
Max. lamp number on MCB B10 A - CCG with compensation	14
Max. lamp number on MCB B16 A	105
Max. lamp number on MCB B16 A - CCG without compensation	105
Max. lamp number on MCB B16 A - CCG with compensation	24
Total harmonic distortion	< 20 %
Power factor λ	0.90

¹⁾ Permitted voltage range

Photometrical data

Luminous flux	3600 lm
Luminous efficacy	150 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤5 sdcm
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1



EPREL data spectral diagram PROF LEDr 4000K

Light technical data

Beam angle	190 °
Warm-up time (60 %)	< 2.00 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	1513.00 mm
Length with base excl. base pins/connection	1500 mm
Diameter	28.00 mm
Base diameter	28 mm
Product weight	252.00 g

Temperatures & operating conditions

Ambient temperature range	-20+50 °C ¹⁾
Maximum temperature at tc test point	85 °C

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70

Rated lamp survival factor at 6,000 h	≥ 0.90	
Additional product data		
Base (standard designation)	G13	
Mercury content	0.0 mg	
Mercury-free	Yes	
Design / version	Frosted	
Capabilities		
Dimmable	Yes 1)	
	Yes 1)	
Only dimmable with LEDVANCE Connected Sensor	Yes 1)	
Only dimmable with LEDVANCE Connected Sensor	Yes ¹⁾	
Only dimmable with LEDVANCE Connected Sensor Certificates & Standards		
1) Only dimmable with LEDVANCE Connected Sensor Certificates & Standards Energy efficiency class	D ¹⁾	
1) Only dimmable with LEDVANCE Connected Sensor Certificates & Standards Energy efficiency class Energy consumption	D ¹⁾ 24.00 kWh/1000h	

Order reference

LOGISTICAL DATA	
Temperature range at storage	-20+80 °C

LEDTUBE T8 EM C

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	Yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No

Correlated colour temperature type	SINGLE_VALUE
Standby power	<0.5 W
Claim of equivalent power	No
Length	1513.00 mm
Height	28.00 mm
Width	28.00 mm
Chromaticity coordinate x	0.382
Chromaticity coordinate y	0.,380
R9 Colour rendering index	0.00
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	1399432
Model number	AC46522

Accessories Mandatory

Product image	Product name	EAN
	CONNECTED SENSOR HB	4058075232983
	CONNECTED SENSOR LB	4058075232969
CONTROL OF THE PROPERTY OF THE	CONNECTED SENSOR REMOTE CONTROL	4058075374034

Safety advice

- Not suitable for operation with electronic control gear.
- $\ \, {\sf Operation}\ in\ {\sf outdoor}\ applications\ in\ {\sf suitable}\ damp-proof\ luminaires\ possible\ according\ to\ data\ sheet\ and\ installation\ instruction.$
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- All electrical connections must be made by a qualified person.
- Disconnect mains before installation.
- Not suitable for emergency lighting.

DOWNLOAD DATA

ments and certificates		Document name	
lser instruction / safety instructions		LEDTUBE T8 EM CON P	
information		Informationstext 18 Abs 4 ElektroG	
Declarations of conformity		LED TUBES T8 EM CON	
Declarations of conformity UKCA		LED TUBES T8 EM CON	
Photometric and lighting design files		Document name	
IES file (IES)		LEDTUBE T8 EM CON P 1500 24W 840 LEDV	
LDT file (Eulumdat)		LEDTUBE T8 EM CON P 1500 24W 840 LEDV	
UGR file (UGR table)		LEDTUBE T8 EM CON P 1500 24W 840 LEDV	
Light distribution curve type polar		LEDTUBE T8 EM CON P 1500 24W 840 LEDV	
Spectral power distribution		EPREL data spectral diagram PROF LEDr 4000K	
or touto	Dogument name		
# IEXIS	DOCUMENT NAME		
er documents	LED TUBE T8 EM CONNECTED P 1500 mm 24W 840-EN		
	ations of conformity ations of conformity UKCA metric and lighting design file (IES) e (Eulumdat) distribution curve type polar ral power distribution r texts	ations of conformity ations of conformity UKCA metric and lighting design files e (Eulumdat) die (UGR table) distribution curve type polar ral power distribution r texts Document name	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075824010	Sleeve 1	1,605 mm x 29 mm x 29 mm	286.00 g	1.35 dm ³
4058075824027	Shipping box 10	1,652 mm x 210 mm x 115 mm	3702.00 g	39.90 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For current information see www.ledvance.com/ledtube

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.