


# PRODUCT DATASHEET Endura Classic E27 IP65 Radick Wall Dark Grey

Endura Classic IP65 E27 | Wall luminaires with dark grey aluminum housing, IP65 protection, frosted diffuser and E27 socket



## Areas of application

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

#### **Product benefits**

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation

## Product features

- Die-cast aluminum housing
- Frosted diffuser
- Anthracite housing color
- Type of protection: IP65

# TECHNICAL DATA

# Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	T .
Operating mode	Mains voltage

# Dimensions & Weight

Length	110.00 mm
Width	108.00 mm
Height	250.00 mm
Product weight	1100.00 g



ENDURA CLASSIC RADICK W E27 IP65

# Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
With light source	No
Replaceable light source	No
Holder designation	E27

## Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

## Additional product data

Product remark	Maximum bulb wattage: 18W (15W LED)	
Number of illuminants	1	

#### **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

## **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	ENDURA CLASSIC RADO RADICK	
PDF	Legal information	Safety insert G11219578	
PDF	Declarations of conformity	Endura Classic IP65	
PDF	Declarations of conformity UKCA	Endura Classic IP65	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854447549	Folding box	118 mm x 122 mm x 262 mm	1300.00 g	3.77 dm <sup>3</sup>
4099854447556	Shipping box 4	270 mm x 260 mm x 295 mm	5200.00 g	20.71 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.