nie server returned a soo internal server Error.

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

PRODUCT DATASHEET FL FLEX DA P 80W 840 A45X140 WAL

FLOODLIGHT FLEX DALI ASYMMETRIC 45 X 140 | DALI D4i floodlight with very wide beam, asymmetric light distribution for area lighting



Areas of application

- Coastal areas, like ports
- General outdoor area lighting
- Parking
- Suitable for indoor and outdoor sports facilities
- Architectural lighting
- Industry
- Direct replacement for luminaires using HID lamps

Product benefits

- Corrosion resistance C5: tested in environments with high salinity
- Serviceable luminaire: LED driver can be replaced
- Flexible application due to a range of different lumen packages and beam angles
- $\,$ $\,$ 3 cable entries for flexible use and easy connection between luminaires
- Integrated breather for preventing condensation inside the luminaire
- $-\,$ Energy savings of up to 91 % compared to halogen lamp floodlights
- Energy savings of up to 51 % compared to luminaires that use conventional discharge lamps
- No upper light output ratio (ULOR 0%) when mounted at 0° tilt
- Intelligent design of the water drain to prevent standing water
- Simple angle adjustment by locking every 2.5°
- Clear angular degree indication
- Key hole to ensure ease of installation

Product features

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

The server returned a 300 internal berver Entor.

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

- Corrosion resistance C5 based on 1,500 hours salt mist spray test
- High luminous efficacy: up to 156 lm/W
- DALI D4i drivers for smart city applications
- Daisy chaining possible
- High surge protection: up to 10 kV (L/N-PE), 6 kV (L-N)
- High lifetime (L70/B50): up to 120,000 h (at 25 °C)
- Lumen packages up to 70000 lm
- Additional 2200 K color temperature version available

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

The Server returned a 300 internal Server Error .

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

TECHNICAL DATA

Electrical data

Nominal wattage	80.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	364.000 mA
Inrush current	123 A
Inrush current time T _{h50}	132 µs
Max. number of luminaires per miniature circuit breaker B16	8
Max. number of luminaires per miniature circuit breaker C10	8
Max. number of luminaires per miniature circuit breaker C16	14
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	I .
Surge capability (L-N)	6 kV
Surge capability (L/N-Ground)	10 kV
Operating mode	Integrated LED driver
Dimming interface	DALI-2 / IoT

Photometrical data


Luminous flux	12000 lm
Luminous efficacy	150 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	5 sdcm
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	45 ° x 140 °

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

The Server returned a 300 internal Server Error .

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.



FL FLEX DA P 80W 840 A45X140 WAL LEDV

Dimensions & Weight

Length	479.00 mm
Width	304.00 mm
Height	67.00 mm
Product weight	4700.00 g



FL FLEX P WAL

Materials & Colors

Product color	White aluminum
Housing color	White aluminum
RAL Color (most similar)	RAL 9017
Body material	Aluminum
Cover material	Glass
Light emitting surface material	Glass

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

nie server returned a soo internal server Error .

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30+50 °C	
Temperature range at storage	-30+80 °C	
Type of connection	Screwless terminal	
Type of protection	IP66	
Protection class IK (shock resistance)	IK08	
Corrosion resistance class acc. to EN 12944	C5	
Dimmable	Yes	
Type of dimming	DALI D4i	
IoT ready	Support of DALI data type PART 251, 252, 253 1)	
Mounting type	Surface	
Mounting location	Wall / Pole / Floor / Ceiling	
Application environment	Outdoor	
Adjustable	Yes	
With light source	Yes	
Replaceable light source	No	

¹⁾ Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud

Lifespan

Lifespan L70/B50 at 25 °C	120000 h ¹⁾
Lifespan L80/B10 at 25 °C	100000 h ¹⁾
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	50000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	2800 mA
ECG - Output ripple current	< 10 %

Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EPD
Luminaire with limited surface temperature, "D sign"	Yes

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

The Server returned a 300 internal Gerver Error .

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

EPD	LEDV-00046-V01.01-EN

Additional product data

Added function	VIVARES
----------------	---------

Accessories Optional

Product image	Product name	EAN
	FL TRAVERSE 1/2 42/60/76MM	4099854680038
	FL FLEX ADAPTER SOCKET ZHAGA	4099854680076
	FL FLEX ADAPTER SOCKET NEMA	4099854680113

EQUIPMENT / ACCESSORIES

- Delivery without cables
- Second cable gland included
- 2 rubber inserts for 6,5 7,5 mm cables included

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	FL FLEX P DALI	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF	Legal information	Safety Insert G11205497	
PDF	Legal information	LSI FL FLEX DALI	
PDF	Legal information	FL FLEX DA P	

Oops! An Error Occurred

The server returned a "500 Internal Server Error".

ne server returned a soo internal server Error .

Something is broken. Please let us know what you were doing when this error occurred. We will fix it as soon as possible. Sorry for any inconvenience caused.

	Documents and certific	ates Document name			
PDF	Declarations of conform	nity	CE FL FLEX P		
PDF	Declarations of conform	nity UKCA	JKCA UKCA FL FLEX P		
PDF	Certificates		ENEC FL FLEX P		
PDF	EU Data Act		DALI LED Driver and Luminaires		
	Photometric and lighting design files		Document name		
ES	IES file (IES)		FL FLEX DA P 80W 840 A45X140 WAL LEDV		
	LDT file (Eulumdat)		FL FLEX DA P 80W 840 A45X140 WAL LEDV		
	ULD file (DIALux)		FL FLEX DA P 80W 840 A45X140 WAL		
	ROLF file (RELUX)		FL FLEX DA P 80W 840 A45X140 WAL		
	Light distribution curve	type polar	FL FLEX DA P 80W 840 A45X140 WAL LEDV		
	CAD/BIM files		Document name		
	BIM Revit 3D		Floodlight Flex		
	CAD STEP 3D		FL FLEX 80W		
	Tender texts	Document name			
	Tender documents	FLOODLIGHT FLEX DALI ASYMMETRIC 45 X 140 80W 840 A45X140 WAL-en			

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854373268	Shipping box	557 mm x 342 mm x 114 mm	5844.00 g	21.72 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Oops! An Error Occurred

The server returned a "500 Internal Server Error".