

# PRODUCT DATASHEET Ceiling Fan Grill Square 55W CCT White

Ceiling fan grill | LED Ceiling Fan Grill that combines light and ventilation



### Areas of application

- Indoor
- Living areas (living rooms, dining rooms, bedrooms etc.)

### Product benefits

- Airflow suitable for 13-20 m<sup>2</sup>
- Set color temperature according to daytime and usage (dining, relaxing, social events...)
- Set light output from 0-100% for personal comfort
- Pleasant use during sleeping phase (low noise on low level speed)
- Aesthetic appearance of a ceiling luminaire
- Summer / winter mode
- 5 years guarantee

### Product features

- Airflow: max 700 m<sup>3</sup>/h
- Speed levels: 1 6 steps
- Timer: 1 h / 2 h / 4 h
- Control unit: remote control
- Motor type: DC
- Adjustable color temperature via Tunable White: 3,000...6,500 K



- Lumen source: 4200 lm
- Dimmable
- Type of protection: IP20

# TECHNICAL DATA

# Electrical data


Nominal wattage	55.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	230.000 mA
Max. number of luminaires per miniature circuit breaker B16	320
Max. number of luminaires per miniature circuit breaker C16	320
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 70 %
Protection class	II
Operating mode	Mains voltage

# Photometrical data

Luminous flux	3100 lm
Total luminous flux of contained light sources	4200 lm
Luminous efficacy	86 lm/W
Color temperature	30006500 K
Light color (designation)	Warm White / Cool Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	175.00 °

# Dimensions & Weight

Length	553.00 mm
Width	553.00 mm
Height	157.00 mm
Product weight	6800.00 g



CEILING FAN GRILL SQUARE CCT WT

### Materials & Colors

Product color	White
Housing color	White
Body material	Steel Plastic
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Mounting type	Surface
Mounting length	533,00 mm
Mounting width	553 mm
With light source	Yes
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

# **Emergency lighting**

### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

### **EQUIPMENT / ACCESSORIES**

- Mounting screws and dowels included
- Safety rope
- Requires 2xAAA batteries (not included)

### Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

### **DOWNLOAD DATA**

	Documents and certificates Document name	
PDF	User instruction / safety instructions	CEILING FAN GRILL
PDF	Legal information	Safety insert G11219301
PDF	Declarations of conformity	CEILING FAN GRILL
PDF	Declarations of conformity UKCA	CEILING FAN GRILL

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854445613	Folding box 1	630 mm x 630 mm x 214 mm	8528.00 g	84.94 dm <sup>3</sup>
4099854445620	Shipping box	648 mm x 232 mm x 648 mm	9748.00 g	97.42 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.