

PRODUCT DATASHEET LED Slim Line 78 75 300° DIM 9.5W 827 Clear R7s

LED SLIM LINE R7S DIM | Dimmable slim LED lamps with retrofit base R7s



Areas of application

- General illumination within ambient temperatures from -20...+40 °C
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Fits into most R7s luminaires thanks to excentric base
- Good all-around light emission
- Lower thermal output (compared with the standard reference product)
- Very long lifetime of up to 25,000 h
- Four year guarantee
- Lower energy consumption than incandescent or halogen lamps

Product features

- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- LED alternative to conventional R7s lamps
- Good quality of light; color rendering index Ra; ≥ 80; constant chromaticity





TECHNICAL DATA

Electrical data

Nominal wattage	9.5 W
Construction wattage	9.50 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	75 W
Nominal current	45 mA
Type of current	AC
Inrush current	5.88 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	28
Max. lamp number on MCB B16 A	36
Total harmonic distortion	25 %
Power factor λ	> 0.50

Photometrical data

Luminous flux	1055 lm
Luminous efficacy	111 lm/W
Lumen main.fact.at end of nom.life time	0.96
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



349927_2700K_Evl_5630.eps

Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	78.00 mm
Diameter	20.00 mm
Maximum diameter	20 mm
Product weight	25.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	89 °C

Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.96

Additional product data

Base (standard designation)	R7s
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmoble	v 1)
Diminable	Yes 17

¹⁾ Check dimmer compatibility at ledvance.com/compatibility

Certificates & Standards

Energy efficiency class	E 1)
Energy consumption	10.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG1

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	LESLIM7875D 9,5
LOGISTICAL DATA	

Temperature range at storage -20...+80 °C

Energy labelling regulation data acc EU 2019/2015		
Lighting technology used	LED	
Non-directional or directional	NDLS	
Mains or non-mains	MLS	
Light source cap-type (or other electric interface)	R7s	
Connected light source (CLS)	No	
Color-tuneable light source	No	
Envelope	No	
High luminance light source	No	
Anti-glare shield	No	

Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Claim of equivalent power	Yes
Length	78.00 mm
Height	20.00 mm
Width	20.00 mm
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.70
LED light source replaces a fluorescent light source	No
EPREL ID	2201955,2506949
Model number	AC71615,AC92030

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Declarations of conformity	LED special lamps	
PDF	Declarations of conformity UKCA	LED special lamps	
	Photometric and lighting design files	Document name	
	Spectral power distribution	349927_2700K_Evl_5630.eps	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854503597	Folding box	30 mm x 49 mm x 130 mm	22.00 g	0.19 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854503603	Shipping box	112 mm x 111 mm x 106 mm	181.00 g	1.32 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.osram-lamps.com/guarantee
- For further products and actual information concerning LED lamps see www.osram-lamps.com/led-lamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.