

PRODUCT DATASHEET LED Star Classic A 200 24.9W 827 Frosted E27

LED PCR LAMP WITH CLASSIC A | LED lamps with recycled plastic



Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

Product features

- LED alternative to conventional lamps
- Mercury-free lamps






TECHNICAL DATA

Electrical data

Nominal wattage	24.9 W
Construction wattage	24.90 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	200 W
Nominal current	205 mA
Type of current	AC
Inrush current	18.6 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	20
Max. lamp number on MCB B16 A	26
Total harmonic distortion	124 %
Power factor λ	0.56

Photometrical data

Luminous flux	3452 lm
Luminous efficacy	138 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



SPECTRAL POWER DISTRIBUTION RGBTW 24W 2700K

Light technical data

Beam angle	200 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	184.00 mm
Diameter	90.00 mm
Maximum diameter	90 mm
Product weight	100.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	100 °C

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Certificates & Standards

Energy efficiency class	D 1)
Energy consumption	25.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG0

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	LEDSCLA200 24,9
-----------------	-----------------

LOGISTICAL DATA

|--|

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE

Standby power	0.00 W
Claim of equivalent power	Yes
Length	184.00 mm
Height	90.00 mm
Width	90.00 mm
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.888
LED light source replaces a fluorescent light source	No
EPREL ID	671015,2192486,2505603
Model number	AC36025,AC69317,AC91931

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

Spectral power distribution

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	LED CL A FR 200 lamp series
PDF	Declarations of conformity	LED lamp
PDF	Declarations of conformity UKCA	LED lamp
	Photometric and lighting design files	Document name

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
--------------	------------------------------	--------------------------------------	--------------	--------

SPECTRAL POWER DISTRIBUTION RGBTW 24W 2700K

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075659667	Folding box	93 mm x 93 mm x 188 mm	251.00 g	1.63 dm ³
4058075659674	Shipping box	202 mm x 196 mm x 200 mm	740.00 g	7.92 dm ³
4099854761744	Shipping box 4	212 mm x 204 mm x 200 mm	1062.00 g	8.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.