

# PRODUCT DATASHEET LED Star Classic A 40 4.9W 865 Frosted E27

LED PCR LAMP WITH CLASSIC A | LED lamps with recycled plastic



#### Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

#### **Product features**

- LED alternative to conventional lamps
- Mercury-free lamps






### TECHNICAL DATA

### Electrical data

| Nominal wattage                        | 4.9 W    |
|--|----------|
| Construction wattage                   | 4.90 W   |
| Nominal voltage                        | 220240 V |
| Operating mode                         | AC Mains |
| Claimed equiv. conventional lamp power | 40 W     |
| Nominal current                        | 42 mA    |
| Type of current                        | AC       |
| Inrush current                         | 11.2 A   |
| Operating frequency                    | 5060 Hz  |
| Mains frequency                        | 5060 Hz  |
| Max. lamp number on MCB B10 A          | 35       |
| Max. lamp number on MCB B16 A          | 45       |
| Total harmonic distortion              | 140 %    |
| Power factor $\lambda$                 | 0.54     |

### Photometrical data

| Luminous flux                           | 470 lm        |
|---|---------------|
| Luminous efficacy                       | 95 lm/W       |
| Lumen main.fact.at end of nom.life time | 0.93          |
| Light color (designation)               | Cool Daylight |
| Color temperature                       | 6500 K        |
| Color rendering index Ra                | 80            |
| Light color                             | 865           |
| Standard deviation of color matching    | ≤6 sdcm       |
| Flickering metric (Pst LM)              | 1.0           |
| Stroboscope effect metric (SVM)         | 0.4           |



Spectral graph CLASSIC A 865

# Light technical data

| Beam angle          | 200 °    |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

# Dimensions & Weight



| Overall length   | 105.00 mm |
|------------------|-----------|
| Diameter         | 59.00 mm  |
| Maximum diameter | 59 mm     |
| Product weight   | 19.00 g   |

# Temperatures & operating conditions

| Ambient temperature range            | -20+40 °C |
|--------------------------------------|-----------|
| Maximum temperature at tc test point | 100 °C    |

# Lifespan

| Lifespan L70/B50 at 25 °C                    | 15000 h |
|--|---------|
| Number of switching cycles                   | 100000  |
| Lumen maintenance at end of service lifetime | 0.93    |

### Additional product data

| Base (standard designation) | E27  |
|-----------------------------|--|
| Mercury content             | 0.0 mg   |
| Mercury-free                | Yes  |
| Design / version            | Frosted  |
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

# Capabilities

| Dimmable                 | No |  |
|--------------------------|----|--|
| Certificates & Standards |    |  |

| Energy efficiency class                      | F 1)            |
|--|-----------------|
| Energy consumption                           | 5.00 kWh/1000h  |
| Type of protection                           | IP20            |
| Standards                                    | CE / UKCA / EAC |
| Photobiological safety group acc. to EN62778 | RG1             |

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Country-specific categorizations

Order reference

| LOGISTICAL DATA              |            |
|------------------------------|------------|
| Temperature range at storage | -20 ±80 °C |

LEDSCLA40 4,9W/

# Energy labelling regulation data acc EU 2019/2015

| Lighting technology used                            | LED          |
|---|--------------|
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | MLS          |
| Light source cap-type (or other electric interface) | E27          |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope  | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Standby power                                       | 0.00 W       |
| Claim of equivalent power                           | Yes          |
| Length  | 105.00 mm    |
| Height  | 59.00 mm     |
| Width   | 59.00 mm     |
| Chromaticity coordinate x                           | 0.3123       |
| Chromaticity coordinate y                           | 0.3283       |
| R9 Colour rendering index                           | 1            |
| Beam angle correspondence                           | SPHERE_360   |
| Survival factor                                     | 0.90         |

| Displacement factor                                  | 0.934   |
|--|---|
| LED light source replaces a fluorescent light source | No  |
| EPREL ID   | 1403230,523305,1351498,1857052,2192464,2505599  |
| Model number   | AC31147,AC44996,AC24716,AC55980,AC69302,AC91913 |

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

#### DOWNLOAD DATA

|     | Documents and certificates            | Document name                |  |
|-----|---------------------------------------|------------------------------|--|
| POF | Declarations of conformity            | Classic A_B_P 15000h FR      |  |
| PDF | Declarations of conformity            | LED CLASSIC A_P NON-DIM      |  |
| PDF | Declarations of conformity            | LED lamp                     |  |
| PDF | Declarations of conformity UKCA       | LED CLASSIC A_P NON-DIM      |  |
| PDF | Declarations of conformity UKCA       | LED lamp                     |  |
|     |                                       |                              |  |
|     | Photometric and lighting design files | Document name                |  |
|     | Spectral power distribution           | Spectral graph CLASSIC A 865 |  |

#### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075304192 | Folding box<br>1             | 60 mm x 60 mm x 145 mm               | 34.00 g      | 0.52 dm <sup>3</sup> |
| 4058075588806 | Shipping box                 | 202 mm x 134 mm x 120 mm             | 290.00 g     | 3.25 dm <sup>3</sup> |
| 4058075304208 | Shipping box<br>10           | 303 mm x 125 mm x 120 mm             | 472.00 g     | 4.55 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.