

# PRODUCT DATASHEET LED Spot Brick 4xGU10 Plate White and Wood

LED Spot Brick | Ceiling mounted luminaires made with mixed materials with adjustable GU10 spotlights



### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, bedrooms, basements

#### Product benefits

- High-quality housing with matt white surface
- Flexible thanks to replaceable LED lamps
- Easy mounting

#### **Product features**

- Luminaire family features five versions with up to 4 spot heads
- Housing material: metal and wood
- On/off switch on 1-head version for easy operation
- Adjustable heads




## TECHNICAL DATA

## Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	1
Operating mode	Mains voltage

# Dimensions & Weight

Length	190.00 mm
Width	190.00 mm
Height	116.00 mm
Product weight	720.00 g



LED SPOT BRICK 4XGU10 PL WT

#### Materials & Colors

Product color	White Wood decor
Housing color	White Wood decor
Body material	Steel Rubberwood
Glow Wire Test according to IEC 60695-2-12	650 °C

## Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Adjustable	Yes

With light source	No
Replaceable light source	No
Holder designation	GU10

### **Emergency lighting**

Type of emergency operation test	None
----------------------------------	------

#### Certificates & Standards

Sta	ndards	CE / UKCA
Lun	ninaire with limited surface temperature, "D sign"	No
Ball	I shot safe	No

### Additional product data

Product remark	Maximum bulb wattage: 5 W LED / Available from October 2025	
Number of illuminants	4	

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

#### DOWNLOAD DATA

	Documents and certificates Document name	
User instruction / safety instructions  LED SPOT BRICK G1123893		LED SPOT BRICK G11238936
PDF	Declarations of conformity	LED SPOT CE declaration

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075852525	Folding box 1	97 mm x 232 mm x 232 mm	896.00 g	5.22 dm <sup>3</sup>
4058075852532	Shipping box 4	420 mm x 245 mm x 255 mm	4014.00 g	26.24 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.