

PRODUCT DATASHEET Orbis Larios 290mm 16W 830 Click DIM Wood Decor and Black

Orbis Larios | LED ceiling luminaire with plastic ring



Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)

Product benefits

- Aesthetic and functional product design
- Click dim function by wall switch

Product features

- Ceiling luminaire with advanced LED technology
- Click-DIM version: dimmable in three steps by repeated switching
- Color temperature: 3,000 K
- Type of protection: IP20



TECHNICAL DATA

Electrical data


| Nominal wattage | 16.00 W |
|------------------------|---------------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Nominal current | 150.000 mA |
| Power factor λ | 0.50 |
| Protection class | 1 |
| Operating mode | Mains voltage |

Photometrical data

| Luminous flux | 1000 lm |
|--|------------|
| Total luminous flux of contained light sources | 2000 lm |
| Luminous efficacy | 63 lm/W |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | 6 sdcm |
| Flickering metric (Pst LM) | <1 |
| Stroboscope effect metric (SVM) | <0.4 |
| Photobiological safety group acc. to EN62778 | RG0 |

Dimensions & Weight

| Diameter | 290.00 mm |
|----------------|-----------|
| Height | 80.00 mm |
| Product weight | 660.00 g |



ORBIS LARIOS 290 16W 830CLICKD

Materials & Colors

| Product color | Wood decor Black | |
|--|---|--|
| Housing color | Wood decor Black | |
| Body material | Metal | |
| Cover material | Poly methyl methacrylate (PMMA) Acrylonitrile butadiene styrene (ABS) | |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C | |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|--|-----------------------------|
| Temperature range at storage | -20+80 °C |
| Type of connection | Terminal, 3-Pole (L, N, PE) |
| Type of protection | IP20 |
| Protection class IK (shock resistance) | IK03 |
| Dimmable | Yes |
| Type of dimming | 3 DIM |
| Mounting type | Surface |
| Mounting location | Ceiling |
| With light source | Yes |
| Replaceable light source | No |

Lifespan

| Lifespan L70/B50 at 25 °C | 50000 h ¹⁾ |
|----------------------------|-----------------------|
| Number of switching cycles | 15000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Emergency lighting

| Type of emergency operation test | None |
|----------------------------------|------|
| Certificates & Standards | |

| Standards | CE / UKCA |
|--|-----------------|
| Luminaire with limited surface temperature, "D sign" | No |
| Ball shot safe | No |
| Replaceable light source (EPREL) | Not replaceable |

Additional product data

| Product remark | Available from December 2025 |
|----------------|------------------------------|
|----------------|------------------------------|

EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

| Documents and certificates Document name | | Document name |
|--|--|------------------------|
| PDF | User instruction / safety instructions | G11242730 ORBIS LARIOS |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854626814 | Folding box | 88 mm x 313 mm x 313 mm | 1133.00 g | 8.62 dm ³ |
| 4099854626821 | Shipping box 6 | 530 mm x 330 mm x 330 mm | 7518.00 g | 57.72 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.