

# PRODUCT DATASHEET LED Spot Vase 2xG9 Brushed Nickel

LED Spot Vase | Surface mounted luminaires with adjustable G9 spotlights

### Areas of application

- Indoor applications



## Product benefits

- Timeless design
- Flexible thanks to replaceable LED lamps
- Easy mounting

## **Product features**

- Luminaire family features five versions with up to 6 spot heads
- Housing surface made of brushed and chrome nickel
- Adjustable heads
- On/off switch on 1-head version for easy operation
- Diffuser made of glass




# TECHNICAL DATA

# Electrical data

Nominal voltage	220240 V
Mains frequency	50/60 Hz
Protection class	1
Operating mode	Mains voltage

# Dimensions & Weight

Length	340.00 mm
Width	90.00 mm
Height	160.00 mm
Product weight	540.00 g



LED SPOT VASE 2XG9

# Materials & Colors

Product color	Brushed nickel chrome	
Housing color	Brushed nickel chrome	
Body material	Steel	
Glow Wire Test according to IEC 60695-2-12	650 °C	

# Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Ceiling
Adjustable	Yes

With light source	No
Replaceable light source	Yes
Holder designation	G9

## **Emergency lighting**

Type of emergency operation test	None
----------------------------------	------

### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

## Additional product data

Product remark	Maximum bulb wattage: 5 W LED / Available from January 2026
Number of illuminants	2

## Safety advice

- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### DOWNLOAD DATA

	Documents and certificates Document name	
PDF	User instruction / safety instructions	LED SPOT VASE G11239551

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075853027	Folding box 1	102 mm x 132 mm x 352 mm	674.00 g	4.74 dm <sup>3</sup>
4058075853034	Shipping box 4	276 mm x 216 mm x 377 mm	3146.00 g	22.48 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.