

# PRODUCT DATASHEET HALOLINE 2000 W 230 V R7S

HALOLINE® Standard | Double ended halogen lamps with tube base



#### Areas of application

- Ideal for emphasizing and accentuating buildings
- General illumination
- Entrance lighting
- Pathway lighting
- Garden lighting
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Outdoor applications only in suitable luminaires

## **Product benefits**

- Brilliant accent light
- No transformer required
- Contains no mercury

### **Product features**

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index Ra: 100
- Color temperature: 3,000 K
- Burning position: p15




## TECHNICAL DATA

## Electrical data

Nominal wattage	2000.00 W
Construction wattage	2000.00 W
Nominal voltage	230 V

## Photometrical data

Luminous flux	40000 lm
Luminous efficacy	20 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	100
Light color	1030
UV protection	No



349635\_HAL\_ohne\_UVS

# Light technical data

Starting time	0 s
---------------	-----

# Dimensions & Weight

Overall length	331.00 mm
Diameter	12.0 mm
Product weight	26.8 g

## Additional product data

Base (standard designation)	R7s
Mercury-free	Yes
Design / version	Tube

November 04, 2025, 23:14:31 HALOLINE 2000 W 230 V R7S

Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / For outdoor applications and operation in damp locations special approved fixtures are required	
Capabilities		
Dimmable	Yes	
Burning position	p15	
Certificates & Standards		
Energy efficiency class	G	
Energy consumption	2000.00 kWh/1000h	
Country-specific categorizations		
ILCOS	HDG-2000-230-R7s-333	
Order reference	64784 2000W 230	
Lighting technology used  Non-directional or directional	OTHER NDLS	
Energy labelling regulation data acc EU 2019/2015		
Mains or non-mains	MLS	
Light source cap-type (or other electric interface)	R7s	
Connected light source (CLS)	No	
Color-tuneable light source	No	
Envelope	No	
High luminance light source	No	
Anti-glare shield	No	
Claim of equivalent power	No	
Length	331.00 mm	
Height	12.0 mm	
Width	12.0 mm	
Chromaticity coordinate x	0.444	
Chromaticity coordinate y	0.406	
Beam angle correspondence	SPHERE_360	
EPREL ID	714422,1635411	
Model number	AC35337,AC54070	

# Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.
- Not designed as a replacement for conventional lighting in private household.

#### **DOWNLOAD DATA**

	Documents and certificates Document name		
PDF	Declarations of conformity	Traditional lamp	
PDF	Declarations of conformity	CE Declaration R7s	
	Photometric and lighting design files	Document name	
	Spectral power distribution	349635_HAL_ohne_UVS	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300004204	Folding box 1	26 mm x 26 mm x 378 mm	38.80 g	0.26 dm <sup>3</sup>
4050300214481	Shipping box 12	391 mm x 86 mm x 121 mm	562.60 g	4.07 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.