

PRODUCT DATASHEET L 22 W/865 G10Q

LUMILUX® T9 C | Circular fluorescent lamps 29 mm, with G10Q base



Areas of application

- Public buildings
- Restaurants
- Industry
- Shops
- Supermarkets and department stores
- Hotels

Product benefits

- Excellent uniform illumination with no shadows

Product features

- Good color rendering index
- Single-ended round fluorescent lamp
- Dimmable






TECHNICAL DATA

Electrical data

| Nominal wattage | 22 W |
|----------------------|---------|
| Construction wattage | 22.90 W |
| Nominal voltage | 62 V |
| Nominal current | 0.4 A |

Photometrical data

| Luminous flux | 1150 lm |
|---------------------------|--------------------|
| Luminous efficacy | 50 lm/W |
| Light color (designation) | LUMILUX Cool White |
| Color temperature | 6500 K |
| Color rendering index Ra | ≥80 |
| Light color | 865 |
| Rated LLMF at 2,000 h | 0.72 |
| Rated LLMF at 4,000 h | 0.67 |
| Rated LLMF at 6,000 h | 0.65 |
| Rated LLMF at 8,000 h | 0.63 |



Dimensions & Weight

| Overall length | 209.00 mm |
|----------------|-----------|
| Diameter | 216 mm |
| Tube diameter | 29 mm |
| Product weight | 124.4 g |

Lifespan

| Service life | 6300 h ¹⁾ |
|--------------|----------------------|
| | |

| Rated lamp survival factor at 2,000 h | 0.99 |
|---------------------------------------|--------|
| Rated lamp survival factor at 4,000 h | 0.95 |
| Rated lamp survival factor at 6,000 h | 0.83 |
| Rated lamp survival factor at 8,000 h | 0.62 |
| Lifespan B50 | 9000 h |

¹⁾ With preheat ECG

Additional product data

| Base (standard designation) | G10q |
|-----------------------------|-----------------|
| Mercury content | 4.8 mg |
| Design / version | LUMILUX version |

Capabilities

Certificates & Standards

| Energy efficiency class | G |
|-------------------------|-----------------|
| Energy consumption | 23.00 kWh/1000h |

Country-specific categorizations

| ILCOS | FSC-22/865-E-G10q-29/216 |
|-----------------|--------------------------|
| Order reference | L 22W/865 C G10 |

Energy labelling regulation data acc EU 2019/2015

| Lighting technology used | OTHER_FL |
|---|--------------|
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Light source cap-type (or other electric interface) | G10q |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 209.00 mm |
| Height | 216 mm |

| Width | 216 mm |
|---------------------------|------------|
| Chromaticity coordinate x | 0,313 |
| Chromaticity coordinate y | 0,337 |
| Beam angle correspondence | SPHERE_360 |
| EPREL ID | 546413 |
| Model number | AC34188 |

EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic and conventional control gears

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|----------------------------|--|
| PDF | Declarations of conformity | EC Declaration of Conformity - 2021 9C1-4077059-EN-01 - T9 C |
| PDF | Certificates | EAC N RU D-DE.PA01.B.25780_21 23.07.2021-22.07.2026 - FL Special |
| PDF | Certificates | EAC RU C-DE HA10.B.00671 16 08 2018 15 07 2023 Expert Sertifikaciya FL |

| Photometric and lighting design files | Document name |
|---------------------------------------|---------------|
| Spectral power distribution | 349641_FL_865 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4008321581105 | Sleeve 1 | 225 mm x 212 mm x 38 mm | 192.80 g | 1.81 dm ³ |
| 4008321581112 | Shipping box 12 | 450 mm x 238 mm x 227 mm | 2708.60 g | 24.31 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.