

# PRODUCT DATASHEET DR DS-P -40/220-240/1A0

LED DRIVER DIP-SWITCH | Constant current LED driver with dip-switch current setting



#### Areas of application

- Suitable for LED luminaires and LED modules
- Applicable for luminaires of protection classes I and II
- For indoor SELV installations
- Offices, shopping centers, hospitals, restaurants, hotels
- Suitable for a broad range of luminaires (by broad range of dip switch currents)

#### Product benefits

- High flexibility due to adjustable output currents via dip switch
- Low flickering enables high light quality as well as good visual comfort
- 5 years guarantee
- Slim housing for narrow installations
- High efficiency and reliability

#### **Product features**

- Available in 20 W, 30 W, 40 W
- Independent installation with optional Cable Clamp Kit
- Lifetime: up to 50,000 h (at max. tc temperature)
- Type of protection: IP20
- Low ripple current < 5%
- Supply voltage: 220...240 V
- Operating frequency: 50/60 Hz
- Safety according to EN 61347-1, 61347-2-3, 61347-2-13, 62384
- Immunity according to EN 61547

#### **TECHNICAL DATA**

## Electrical data

Nominal output power	40 W <sup>1)</sup>
Nominal voltage	220240 V
Nominal output voltage	2540 V <sup>2)</sup>
Input voltage AC	198264 V <sup>3)</sup>
Input voltage DC	230280 V
U-OUT (working voltage)	2540 V
Type of current	AC/DC
Nominal current	280 mA
Nominal output current	700 mA / 750 mA / 800 mA / 850 mA / 900 mA / 950 mA / 1000 mA / 1050 mA <sup>4)</sup>
Inrush current	25 A
Output current tolerance +/- 5 %	
Output ripple current (100 Hz) $\leq$ 5 %	
Mains frequency	50/60 Hz
Total harmonic distortion	≤ 15 % <sup>5)</sup>
Power factor $\lambda$	≥ 0.95 <sup>5)</sup>
ECG efficiency	89 % <sup>5)</sup>
Device power loss	5.19 W <sup>5)</sup>
Max. ECG no. on circuit breaker 10 A (B)	24
Max. ECG no. on circuit breaker 16 A (B)	38
Max. ECG no. on circuit breaker 25 A (B)	60
Surge capability (L-N)	1.5 kV
Galvanic isolation	SELV

<sup>1)</sup> Partial load 18...42 W


# Dimensions & Weight

<sup>2)</sup> Maximum 55 V

<sup>3)</sup> Permitted voltage range

<sup>4) &</sup>lt;sub>±5%</sub>

<sup>5)</sup> At full load, 220...240 V, 50 Hz



Length	97.80 mm
Mounting hole spacing, length	88.00 mm
Width	44.00 mm
Height	25.50 mm
Cable cross-section, input side	0.751.5 mm <sup>2</sup>
Cable cross-section, output side	0.51.5 mm <sup>2</sup>
Prewired	No
Wire preparation length, input side	8.09.0 mm
Wire preparation length, output side	8.0 mm
Product weight	83.00 g

#### Colors & materials

Product color	White
Casing material	Plastic
Body material	Plastic

## Temperatures & operating conditions

Ambient temperature range	-20+50 °C <sup>1)</sup>
Maximum temperature at to test point	< 85 °C
Max.housing temperature in case of fault	< 95 °C
Temperature range in operation	-20+50 °C <sup>1)</sup>
Permitted rel. humidity during operation	1093 %

<sup>1) -20...+45 °</sup>C at 1050 mA

## Lifespan

ECG lifetime	50000 h
Number of switching cycles	25000

## Additional product data

Encapsulated	No

## Capabilities

Dimmable	No
Overheating protection	No
Overload protection	Yes
Short-circuit protection	Yes
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	1,11
Suitable for emergency lighting	No
Type of connection, output side	Push terminal

#### Certificates & Standards

Approval marks – approval	CE / CB / ENEC / EAC	
Standards	Acc. to EN 61347-2-13 / Acc. to EN 61347-1 / Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 61000-3-2 / Acc. to EN 62384	
Protection class	П	
Type of protection	IP20	

#### LOGISTICAL DATA

Temperature ran	ge at storage	-20+85 °C

## Accessories Optional

Product image	Product name	EAN
	DR AY DS-P-CLAMP DUO	4099854077937

#### **EQUIPMENT / ACCESSORIES**

- Cable Clamp Kit to ensure propper strain relief

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Disconnect mains before installation.
- Do not open enclosure-housing.

#### **DOWNLOAD DATA**

Documents and certificates Document name		Document name	
User instruction / safety instructions  DR DS-P		DR DS-P	
PDF	Legal information	Safety Insert G11205498	
PDF	Declarations of conformity	DR DS P	
POF	Declarations of conformity UKCA	DR DS P	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854077111	Folding box 1	106 mm x 47 mm x 31 mm	98.00 g	0.15 dm <sup>3</sup>
4099854077128	Shipping box 10	235 mm x 205 mm x 80 mm	1194.00 g	3.85 dm <sup>3</sup>
4099854077135	Shipping box 50	470 mm x 255 mm x 240 mm	5970.00 g	28.76 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For Guarantee see www.ledvance.com/guarantee

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.