

PRODUCT DATASHEET Submarine Integrated 1.2M 36W 4000K

SUBMARINE® Integrated | Damp-proof luminaires with integrated LED module



Areas of application

- Basements, garages, warehouses

Product benefits

- Easy and quick installation
- Very homogenous light
- Extremely bright

Product features

- Dust-protected and jet-proof (IP65)
- Not dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	36.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	157.000 mA
Max. number of luminaires per miniature circuit breaker B16	27
Max. number of luminaires per miniature circuit breaker C16	38
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	II .
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	3000 lm
Total luminous flux of contained light sources	3600 lm
Luminous efficacy	83 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80
Standard deviation of color matching	< 5 sdcm
Photobiological safety group acc. to EN62778	RG0
Beam angle	120°

Dimensions & Weight

Length	1180.00 mm
Width	86.00 mm
Height	66.00 mm
Product weight	1210.00 g



Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C	
Type of connection	Terminal, 2-Pole (L, N)	
Type of protection	IP65	
Protection class IK (shock resistance)	IK06	
Dimmable	No	
Mounting type	Surface	
Application environment	Indoor	
With light source	Yes	
Replaceable light source	No	

Lifespan

Number of switching cycles	25000

Certificates & Standards

Standards	CE / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates Document name		
PDF	User instruction / safety instructions	SUBMARINE LED I	
PDF	Legal information	Safety insert G11219279	
PDF	Declarations of conformity	CE Declaration SubMARINE LED I	
POF	Declarations of conformity UKCA	ons of conformity UKCA Fixed LUM	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854428937	Folding box 1	89 mm x 1,210 mm x 69 mm	1500.00 g	7.43 dm³
4099854428944	Shipping box 8	1,230 mm x 200 mm x 304 mm	12000.00 g	74.78 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.